

Sarria® First



If you are looking for a smooth and uniform finish, Sarria First is the perfect choice. Its deep blue-black unfading colour and flat surface attractively speckled with inert mineral inclusions perfectly complement every project.



Product information



Product profile

SSQ Sarria First is a popular product amongst roofing contractors. Sourced from North West Spain, in the heart of the quarrying region of Orense, Sarria has a rich blue-black colour that will not fade even in the strongest sunlight.

SSQ Sarria has been tested in accordance with BS EN 12326, carries the CE marking and is classified as 'W1-T1-S1'.

Each pallet leaving the quarry is subject to inspection and certification. Independent random spot checks are also carried out to ensure the best quality.

* Test results are available on request

Appearance

SSQ Sarria has a blue-black unfading colour and a smooth texture characterised by a distinctive grain. It is speckled with inert mineral inclusions that will not leach or hole over time.

Guarantee

SSQ Sarria First blue-grey roofing slate is covered by a 50-year guarantee.

* Guarantees to be requested within 6 months of the date of completion of the roof.

Minimum headlap for fixing slates with nails or hooks according to BS 5534:2003
Moderate exposure (< 56.5 l/m² per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
600 x 300	115	105	95	85	80	70	60	55	–
500 x 250	115	105	95	85	80	70	60	55	50
400 x 250	–	–	–	–	80	70	60	55	50
400 x 200	–	–	–	–	80	70	60	55	50

Severe exposure (≥ 56.5 l/m² per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
600 x 300	145	130	120	110	100	90	80	70	–
500 x 250	–	130	120	110	100	90	80	70	65
400 x 250	–	–	–	–	100	90	80	70	65
400 x 200	–	–	–	–	100	90	80	70	65

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
600 x 300	5 - 6	3024
500 x 250	5 - 6	2100
400 x 250	5 - 6	1680
400 x 200	5 - 6	1344

Coverage

Nail fixing method

Size (mm)	Lap (mm)											
	50	65	75	80	90	100	110	115	120	130	140	150
	Number of slates/m ²											
600 x 300	12.1	12.5	12.7	12.8	13.1	13.3	13.6	13.7	13.9	14.2	14.5	14.8
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0	21.6	22.2	–
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	–	–	–
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	35.1	35.7	–	–	–

(NB: No allowance has been made for wastage*)

Hook fixing method

Size (mm)	Lap (mm)									
	50	65	75	80	85	90	95	100	105	
	Number of slates/m ²									
600 x 300	12.1	12.5	12.7	12.8	12.9	13.1	13.2	13.3	13.5	
500 x 250	17.8	18.4	18.8	19.0	19.3	19.5	19.8	20.0	20.3	
400 x 250	22.9	23.9	24.6	25.0	25.4	25.8	26.2	26.7	27.1	
400 x 200	28.6	29.9	30.8	31.3	31.7	32.3	32.8	33.3	33.9	
Size (mm)	Lap (mm)									
	110	115	120	125	130	135	140	145	150	
	Number of slates/m ²									
600 x 300	13.6	13.7	13.9	14.0	14.2	14.3	14.5	14.6	14.8	
500 x 250	20.5	20.8	21.0	21.3	21.6	21.9	22.2	22.5	–	
400 x 250	27.6	28.1	28.6	29.1	–	–	–	–	–	
400 x 200	34.5	35.1	35.7	36.4	–	–	–	–	–	

(NB: No allowance has been made for wastage*)

* Please refer to the SSQ Natural Roofing Slate Design and Fixing Guide for full details (available on www.ssqgroup.com).

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: Unit 13/14, Workwest, 301 Glen Rd, Belfast, BT11 8BU

T: +44 (0) 79 1239 0505

SSQ Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

E: info@ssq.co.uk W: www.ssqgroup.com



EXCLUSIVELY NATURAL SLATE