

SSQ Del Carmen roofing slate is known for its smooth and uniform finish, deep blue-black unfading colour and exceptional technical properties. Del Carmen will crown your building in a truly spectacular style.



Product information

Product profile

SSQ Del Carmen slate is mined at the Del Carmen quarry, one of the largest quarries in North-West Spain. The quarry is located in the Cabrera Mountains, an area that contains uninterrupted seams of high-quality slate. SSQ's long-term partnership with the Del Carmen quarry has led to the production of exceptionally high-quality roofing slate for over a decade.

In addition to passing SSQ's own, rigorous quality control tests, SSQ Del Carmen Heavy roofing slate has been tested in accordance with EN 12326, carries the UKCA marking and is classified as 'W1-T1-S1'.*

SSQ Del Carmen roofing slate has been accepted by many of the UK's heritage agencies for use on restoration projects or within conservation areas.

* Test results are available on request



Appearance

SSQ Del Carmen Heavy roofing slate has a distinctive riven texture; the deep blue-black colour is totally natural and will not fade, even in the strongest sunlight.

Guarantee

SSQ Del Carmen Heavy roofing slate is covered by a 100-year guarantee.**

** Guarantees to be requested within 6 months of the date of completion of the roof.

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling

Moderate exposure (< 56.5 l/m2 per spell)*

Size	Rafter pitch										
(mm)	20 °	22.5°	25°	27.5°	30°	35°	40 °	45°	80°		
500 x 250	-	150	120	100	80	70	60	55	50		
400 x 250	-	-	-	-	80	70	60	55	50		

Severe exposure (≥ 56.5 l/m2 per spell)*

Size	Rafter pitch									
(mm)	20 °	22.5°	25°	27.5°	30°	35°	40 °	45°	80°	
500 x 250	-	-	-	130	100	90	80	70	65	
400 x 250	-	_	-	-	100	90	80	70	65	

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
500 x 250	8 - 10	2840
400 x 250	8 - 10	2900

Coverage Nail fixing method

Size	Lap (mm)									
(mm)	50	65	75	80	90	100	110	115	120	
	Number of slates/m ²									
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0	
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	

(NB: No allowance has been made for wastage*)

Hook fixing method

Size	Lap (mm)									
(mm)	50	65	75	80	90	100	110	115	120	
	Number of slates/m ²									
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0	
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	

(NB: No allowance has been made for wastage*)

 Please refer to the SSQ Natural Roofing Slate Design and Fixing Guide for full details (available on www.ssggroup.com).

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept to responsibility for any loss or damage howsover caused that may arise through the reliance being placed on the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request. The information and illustrations in this publication were correct at the time of publication.

The information and illustrations in this publication were correct at the time of publication.

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: 16A Crosshill Road, Crumlin, BT29 4BH T: +44 (0) 79 1239 0505

SSO Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

E: info@ssq.co.uk W: www.ssqgroup.com

