

Domiz® Heavy













If you are looking for a slightly greyer finish to your roof, Domiz is the perfect choice. Its rich blue-grey overtones, coupled with a deep, bold texture, give you a stunning finish every time.



Product information









Product profile

SSQ Domiz blue-grey slate is mined exclusively for SSQ from the Orense region of North-West Spain, offering a high-quality roofing material to the UK market.

In addition to passing SSQ's own, rigorous quality control tests, SSQ Domiz Heavy, blue-grey roofing slate has been tested in accordance with EN 12326, carries the UKCA marking and is classified as 'W1-T1-S1'.*

Appearance

Domiz is rich in blue-grey overtones, coupled with a deep bold texture. The colour is totally natural and will not fade, even in the strongest sunlight or harshest environments.

Guarantee

SSQ Domiz Heavy, blue-grey roofing slate is covered by a 75-year guarantee.**

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling Moderate exposure (< 56.5 l/m2 per spell)*

s	Size mm)	Rafter pitch									
(m		20 °	22.5°	25°	27.5°	30°	35°	40°	45°	80°	
4	00 x 250	-	-	-	-	80	70	60	55	50	
4	00 x 200	-	-	-	-	80	70	60	55	50	
3	50 x 200	-	-	-	-	80	70	60	55	50	

Severe exposure (≥ 56.5 l/m2 per spell)*

Size	Rafter pitch										
(mm)	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°		
400 x 250		-		-	100	90	80	70	65		
400 x 200		-	-	-	120	110	105	100	65		
350 x 200	-	-	-	-	100	90	80	70	65		

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
400 x 250	8-10	2294
400 x 250	7-9	1965
400 x 200	7-9	1545
350 x 200	7-9	1165

Coverage Nail fixing method

Size	Lap (mm)									
(mm)	50	65	75	80	90	100	110	115	120	
	Number of slates/m²									
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	-	-	
350 x 200	33.3	35.1	36.4	37.0	38.5	40.0	41.7	-	_	

(NB: No allowance has been made for wastage*)

Hook fixing method

Size	Lap (mm)									
(mm)	50	65	75	80	90	100	110	115	120	
	Number of slates/m ²									
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	-	-	
350 x 200	33.3	35.1	36.4	37.0	38.5	40.0	41.7	-	-	

(NB: No allowance has been made for wastage*)

* Please refer to the SSQ Natural Roofing Slate Design and Fixing Guide for full details (available on www.ssqgroup.com).

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept no responsibility for any loss or damage howsoever caused that may arise through the reliance being placed on the content of the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request. The information and illustrations in this publication were correct at the time of publication.

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: The YARD Group, 50 Moira Road, Aldergrove, Crumlin, BT29 4JL

T: +44 (0) 79 1239 0505

SSO Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

E: info@ssq.co.uk W: www.ssqgroup.com



^{*} Test results are available on request

^{**} Guarantees to be requested within 6 months of the date of completion of the roof.