



# Montegrís Standard

Montegrís is a grey-green slate perfect if you are looking for that natural finish to your roof.



## Product information

### Product profile

SSQ Montegrís Standard is a rare grey natural slate with a tinge of green. The slates create a unique aesthetic appearance to any building's exterior due to the high contents of fine-grained mica flakes. Sourced from South America, the slates have been tested in accordance with EN 12326 and are classified as 'W1-S1-T1'.\* As a result, Montegrís provides excellent performance levels as a construction material.

\* Test results are available on request

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling Moderate exposure (< 56.5 l/m<sup>2</sup> per spell)\*

| Size (mm) | Rafter pitch |       |     |       |     |     |     |     |     |
|-----------|--------------|-------|-----|-------|-----|-----|-----|-----|-----|
|           | 20°          | 22.5° | 25° | 27.5° | 30° | 35° | 40° | 45° | 80° |
| 500 x 250 | -            | 150   | 120 | 100   | 80  | 70  | 60  | 55  | 50  |

Severe exposure (≥ 56.5 l/m<sup>2</sup> per spell)\*

| Size (mm) | Rafter pitch |       |     |       |     |     |     |     |     |
|-----------|--------------|-------|-----|-------|-----|-----|-----|-----|-----|
|           | 20°          | 22.5° | 25° | 27.5° | 30° | 35° | 40° | 45° | 80° |
| 500 x 250 | -            | -     | -   | 130   | 100 | 90  | 80  | 70  | 65  |

### Size and weight

| Size (mm) | Thickness (mm) | Weight per 1000 (kg) |
|-----------|----------------|----------------------|
| 500 x 250 | 6 - 9          | 2250                 |

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept no responsibility for any loss or damage howsoever caused that may arise through the reliance being placed on the content of the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request. The information and illustrations in this publication were correct at the time of publication.

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: 16A Crosshill Road, Crumlin, BT29 4BH

T: +44 (0) 79 1239 0505

SSO Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

E: info@ssq.co.uk W: www.ssqgroup.com



### Guarantee

SSQ Montegrís Standard roofing slate is covered by a 30-year guarantee.\*\*

\*\* Guarantees to be requested within 6 months of the date of completion of the roof.

### Selection

SSQ Montegrís Standard has a relatively smooth texture, some thickness and flatness variations and requires a high level of sorting and grading.

### Coverage

#### Nail fixing method

| Size (mm) | Lap (mm)                        |      |      |      |      |      |      |      |      |
|-----------|---------------------------------|------|------|------|------|------|------|------|------|
|           | 50                              | 65   | 75   | 80   | 90   | 100  | 110  | 115  | 120  |
|           | Number of slates/m <sup>2</sup> |      |      |      |      |      |      |      |      |
| 500 x 250 | 17.8                            | 18.4 | 18.8 | 19.0 | 19.5 | 20.0 | 20.5 | 20.8 | 21.0 |

(NB: No allowance has been made for wastage\*)

#### Hook fixing method

| Size (mm) | Lap (mm)                        |      |      |      |      |      |      |      |      |
|-----------|---------------------------------|------|------|------|------|------|------|------|------|
|           | 50                              | 65   | 75   | 80   | 90   | 100  | 110  | 115  | 120  |
|           | Number of slates/m <sup>2</sup> |      |      |      |      |      |      |      |      |
| 500 x 250 | 17.8                            | 18.4 | 18.8 | 19.0 | 19.5 | 20.0 | 20.5 | 20.8 | 21.0 |

(NB: No allowance has been made for wastage\*)

\* Please refer to the SSQ Natural Roofing Slate Design and Fixing Guide for full details (available on [www.ssqgroup.com](http://www.ssqgroup.com)).



EXCLUSIVELY NATURAL SLATE

© Registered trademark, SSQ Group, July 2023