



# Matacouta<sup>®</sup> Heavy



Matacouta natural slate has a reputable history in Scotland and is highly regarded for its blue-black colour, traditional riven texture and characteristic grain. Often used on buildings of historical importance, Matacouta is the perfect choice for any project.



# Product information



## Product profile

SSQ Matacouta slate is mined exclusively for SSQ from the La Baña region in North-West Spain. SSQ's long-term relationship with the Matacouta quarry has led to the production of exceptionally high-quality roofing slate and exclusive distribution rights within the UK. SSQ Matacouta roofing slate has been accepted in the past for use on restoration projects or within conservation areas in Scotland.

In addition to passing SSQ's own, rigorous quality control tests, SSQ Matacouta Heavy roofing slate has been tested in accordance with EN 12326, carries the UKCA marking and is classified as 'W1-T1-S1'.\*

\* Test results are available on request

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling

Moderate exposure (< 56.5 l/m<sup>2</sup> per spell)\*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
400 x 250	–	–	–	–	80	70	60	55	50
400 x 220	–	–	–	–	80	70	60	55	50
400 x 200	–	–	–	–	80	70	60	55	50

Severe exposure (≥ 56.5 l/m<sup>2</sup> per spell)\*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
400 x 250	–	–	–	–	100	90	80	70	65
400 x 220	–	–	–	–	100	90	80	70	65
400 x 200	–	–	–	–	120	110	105	100	65

## Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
400 x 250	8 - 10	2116
400 x 220	10 - 12	2307
400 x 220	8 - 10	1875
400 x 200	10 - 12	2307
400 x 200	8 - 10	1875

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept no responsibility for any loss or damage howsoever caused that may arise through the reliance being placed on the content of the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request. The information and illustrations in this publication were correct at the time of publication.

**SSQ Head Office:** 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

**SSQ Northern Irish Office:** 16A Crosshill Road, Crumlin, BT29 4BH

T: +44 (0) 75 9816 3622

**SSO Spanish Office:** C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

For any technical questions or guidance, please email directly [technical@ssq.co.uk](mailto:technical@ssq.co.uk)

**E: [info@ssq.co.uk](mailto:info@ssq.co.uk) W: [www.ssqgroup.com](http://www.ssqgroup.com)**

## Appearance

SSQ Matacouta roofing slate is a deep blue-black colour and has a traditional riven texture. The colour is totally natural and will not fade, even in the strongest sunlight or harshest environments.

## Guarantee

SSQ Matacouta Heavy blue-black roofing slate is covered by a 100-year guarantee.\*\*

\*\* Guarantees to be requested within 6 months of the date of completion of the roof.

## Coverage

### Nail fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m <sup>2</sup>								
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6
400 x 220	26.0	27.1	28.0	28.4	29.3	30.3	31.3	31.9	32.5
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	–	–

(NB: No allowance has been made for wastage\*)

### Hook fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m <sup>2</sup>								
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6
400 x 220	26.0	27.1	28.0	28.4	29.3	30.3	31.3	31.9	32.5
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	–	–

(NB: No allowance has been made for wastage\*)

\* Please refer to the **SSQ Natural Roofing Slate Design and Fixing Guide** for full details (available on [www.ssqgroup.com](http://www.ssqgroup.com)).



EXCLUSIVELY **NATURAL SLATE**